2

FRICTION

THEORY

2.1 INTRODUCTION

When we press our foot on the floor and try to slide it forward we feel that something is opposing or resisting our action of sliding our foot forward.

This force which opposes our action of sliding our foot on the surface of the floor is called friction.

The force of friction : When one object rubs against something else (which may be in any state such as solid, liquid or gas), a force acts on the surfaces in contact which opposes the relative motion between them. This force is called the force of friction. An important rule of friction is that it always acts in a direction to oppose the relative motion. If we pull a block of wood on a surface to the right, the force of friction on the block will be to the left.



Fig. Force of friction is opposite of the applied force

Similarly, a boat propelled to the east by its motor experience water friction to the west. An object falling downward through the air, experiences air friction, called air resistance, in upward direction. The amount of friction between two surface depends on the kinds of material and how much they are pressed together. The force of friction between two rough surfaces is more than that between two smooth surface. Friction is due to roughness of surfaces. All surface on microscopic view, have tiny bumps as shown in the figure.



Fig. Friction results from the mutual contact of irregularities in the surfaces of sliding objects. Even surfaces that appear to be smooth have irregular surfaces when viewed at the microscopic level.

Due to these irregularities in the surfaces, friction appears in solid surfaces. Note **that the force of friction doesn't depend on the area of contact of surfaces**.



Frictional force does not oppose the motion in all cases, infact in some cases the body moves due to it, In the fig., book B moves to the right due to friction between A & B. If book A is totally smooth (i.e., frictionless) the book B does not move to the right. This is because of no force applied on the book B in the right direction.



2.2 FRICTION

Friction is the opposition to motion experienced when two surfaces are in contact move with respect to each other.

Whenever the surface of one body slides over that of another, each exerts a force on the other which opposes the motion of the body. This is called frictional force shown in given figure.



Frictional force comes into play only when two surfaces are in physical contact and is therefore a contact force.



CAUSES OF FRICTION

The friction between any two surfaces is mainly caused by the following factors:

(i) Due to the interlocking of surfaces: No solid surface is perfectly smooth. This means all solid surfaces are rough. The degree of roughness varies from surface to surface. Some are more rough, while some others are less. Even a surface which looks smooth to the naked eyes is actually rough. In the case of highly rough surfaces, the surface roughness can be seen, felt easily.



Roughness of the surfaces in contact can be seen as the presence of hills and valleys in expanded view of a part of the surface is shown in figure.

In the case of surfaces which appear to be smooth, the surface roughness can be seen only with the help of a microscope. A magnified view of the surface roughness is shown alongside. When a body (say, a wooden block) is pulled over another, these 'hills' and 'valleys' interlock with each other and oppose the relative motion between the two bodies. This gives rise to a frictional force. Thus, friction is due to the roughness of the two surfaces in contact.

(ii) **Due to force of adhesion between the two surfaces: Two** rough surfaces when placed together meet only at certain points. The atoms or molecules present at such points of contact attract each other due to electrostatic attractions. These attractions are called forces of adhesion. When one body is made to move over the other, the force of adhesion opposes the motion. This force which opposes the motion also gives rise to frictional force. So, the force of adhesion between the two surfaces gives rise to friction.

2.2.1 Factors Affecting Friction

- 1. Friction depends upon the nature of the surfaces in contact. Smoothness of the contacting surfaces does affect the force of friction between two surfaces in contact.
- 2. The force of friction is directly proportional to the normal force. When a body is moving over a horizontal surface, it presses down against the surface with a force equal to its weight i.e. to the pull of gravity upon it. An increase in the weight of the body causes an increase in the amount of resistance offered to the relative motion of the surface in contact.

3. Friction does not depend on the amount of surface area in contact between the moving bodies. Within limits, friction between two solid surfaces moving with respect to each other does not depend on the relative speed between the two surfaces and the area of contact.

2.2.2 Direction of Frictional Force

When a block is pulled by force F towards the right, the force of friction acts towards the left and when the block is pulled by force F towards the left, the force of friction acts towards the right. So we can say that force of friction always acts in the direction opposite to that of motion or intended motion.

2.3 TYPES OF FRICTION

You must have noticed that when you have to slide a heavy box, it is easy to slide it once the box has started sliding. You may also have noticed that it is much easier to roll a heavy drum than to slide it. On the basis of its nature frictional force can be divided into four types. They are :

- 1.
 Static Friction
 2.
 Limiting Friction
 3.
 Sliding or Dynamic Friction
- 4. Rolling Friction

2.3.1 Definition

- 1. **Static Friction :** The friction that exits between the two surfaces in contact when there is no relative motion between them is called **static friction**.
- 2. Limiting Friction : The maximum force of static friction come into play when one body just slides upon another body is called limiting friction.
- 3. Sliding or Dynamic Friction : The force of friction acting between the two bodies, when they are sliding upon one another with a uniform speed is called dynamic friction or sliding friction.

The friction that exists between a surface sliding on another surface is called the **sliding friction**.

4. **Rolling Friction :** The friction experienced by a body, when it is made to move over bodies like roller or a wheel is called **rolling friction**.

or

When a body rolls on the surface of another, the friction that exists between the surface is known as **rolling friction**.

Experimentally, it has been proved that,

Static friction > Sliding or Dynamic friction > Rolling friction.

It has been demonstrated through the experiment in Activity.

2.3.2 Sliding and Rolling Friction



All other factors remaining the same, sliding an object (like a cylinder) is more difficult than rolling as shown in figure. The frictional force offered when sliding an object is called 'sliding friction' and that offered when rolling an object is called rolling friction.

The fact that rolling friction is smaller than sliding is made use of in a device called 'ball bearing'.



How is rolling friction caused?

- 1. The roller or the wheel deforms [changes the shape] temporarily the surface on which it is rolling, thereby causing a depression, on account of its weight.
- 2. In this process the roller or the wheel itself gets deformed temporarily at the point of contact of the surface of the body.

Because of the above deformations a kind of inclined plane is formed in the direction of motion of the roller or the wheel. Thus, a force is required to overcome this temporary, but continuously forward moving inclined plane. This force applied against the continuously forward moving inclined plane is the equivalent of **rolling friction**.



From the above discussion it is clear **that the smaller the depression formed at the point of contact of wheel or roller with a given surface, the Lesser is the force of rolling friction and vice versa**. Furthermore, rolling friction is far less than the sliding friction. That is why, wherever possible, sliding friction is replaced by rolling friction. This is achieved by using wheels, ball bearing, roller bearings, etc.

2.3.3 Examples of rolling friction

1. When a car or bus or bicycle, moves on the road, a part of its wheels and the surface of the road get continuously deformed. Thus, force has to be applied to overcome this deformation and it is equivalent to the rolling friction.

It is for the same reason that more force is required, when the tyres do not have sufficient air pressure, because deformation produced is very large. Conversely, if the tyres are heavily inflated, the deformation produced is very small, and hence, the rolling friction decreases. However, the ride becomes very bumpy. Furthermore, it becomes difficult to apply brakes as the vehicle does not stay on its path during the application of brakes. 2. The wheels of the train are made of steel and so are the railway tracks. Thus, the deformation produced in them is very small, and hence, they have a very small rolling friction. It is because of this small rolling friction that the trains run very fast.



A steel wheel on railway

3. These days luggage, such as suitcase is provided with tiny wheels. These wheels offer very small amount of rolling friction and are easy to move.



A suitcase with wheels A girl on roller skates

4. Roller skates have tiny wheels. These wheels have very small rolling friction and help fast motion of the skater.



Why is dynamic friction slightly less than the limiting friction?

You know that friction is caused due to the interlocking of the irregularities on the surfaces of two bodies in contact with each other. Now, more force is required to unlock the irregularities between the surfaces of two stationary bodies as compared to the force required to keep the irregularities unlocked between the surfaces of two sliding bodies . Thus, the liming friction is always slightly more than the dynamic friction or dynamic friction is slightly less than the limiting friction. Figure shows a graph between the applied force on the spring balance and the force of friction. The region **AB** in the graph shows static friction, which is self adjusting. **BC** shows the magnitude of limiting friction.



2.3.4 Factors affecting limiting friction

- 1. Limiting friction always opposes the motion of a body and acts in the direction opposite to the direction of applied force.
- 2. Limiting friction depends upon the nature of surfaces in contact with each other.
- 3. Limiting friction increases with the increase in the weight of the body and vice versa.
- 4. Limiting friction is independent of areas of contact between two surfaces, provided the weight of the body and the nature of surfaces do not change.

2.4 EFFECT OF FRICTION

When an object moves in contact with another object, the force of friction can produce following effects.

- (a) Friction opposes motion : The force of friction always acts in the direction opposite to the direction of the applied force. It opposes the motion of the body and tries to stop it. Take the example of a moving car at a constant speed of 60 km/h. If we lift our foot from the accelerator. The car slows down and finally stops. It is because of the force of friction. As a matter of fact, when a vehicle is moving at a constant speed, the energy spent in keeping the vehicle to move at same speed is utilised in overcoming friction of the road.
- (b) Friction produces heat : Take a one rupee coin and hold it from its edge. Rub the coin against the wooden table top. Touch the rubbed side of coin with your hand. What do you observe? The coin feels very hot. It is because the force of friction between the table top and the coin changes into heat energy. It is for the same reason that our palms get warm when rubbed



Burning of meteor

It is for the same reason that our palms get warm when rubbed against each other. Similarly, the cave man produced fire by rubbing a dry wooden stick in a hole of dry wooden block.

It is for the same reason that the jar of a mixer grinder get hot at their moving parts.

The meteors (shooting stars) enter the atmosphere of earth at a very-very high speed. At such speeds, the friction between a meteor and the air is extremely high. Due to this high friction the temperature of the meteor rises to such a high degree that it catches fire and completely burns before reaching the earth. In fact, force of friction of air saves us from the impact of meteors coming from the space.

The spaceships are provided with heat shield at their nose. It is because when spaceships enter the atmosphere, due to friction of air they can catch fire much like meteors. However, the heat shield prevents such a fire due to friction.

(c) Friction causes wear and tear : Try to compare the soles of your new shoes with old shoes. You will notice that the soles of old shoes are worn out. It is because when we walk, material of the soles wears out due to friction.

Similarly, the tyres of all kinds of vehicles wear out due to friction. In fact, all movable parts of all kinds of machines were out. This in turn makes the machines inefficient or useless.



ACTIVITY

Take a heavy wooden block provided with a hook. Place the wooden block on a table top. Attach a spring balance to its hook and pull it slowly towards the right side. You will note that initially the wooden block does not move but the spring balance records the force applied on the wooden block. The force recorded by the spring balance is equal and opposite to the force of friction between the wooden block and the table top.

Next, Increase the force on the spring balance. What do you observe? The wooden block does not move but the spring balance indicates higher value of applied force. Thus, as the wooden block remains static, the applied force is equal and opposite to the force of friction. This suggests that the force of friction in stationary or static state of the body is self-adjusting. This force of friction is known as **static friction**.

Go on increasing the pull on the wooden block, till it starts sliding. Note the reading shown by the spring balance. It will record maximum applied force which is equal and opposite to the force of friction. This maximum force required to make one body just slide over another body is called limiting friction.



Apply the pull on the wooden block in such a way that it gently slides over the table top. What do you observe? The spring balance registers lesser force than the limiting friction. This lesser force that enables the wooden block just slide on the table top is known as **sliding** or **dynamic friction**. This activity explains the meaning of static friction, limiting friction and dynamic friction.

2.5 FRICTION DUE TO LIQUIDS AND GASES

When a solid move in a liquid or a gas, the surface of the solid experiences friction. The frictional force exerted by fluids (liquid or gas) is called drag. It is established that liquids exert less force of friction as compared to the solids. Also, the gases exert the least force of friction as compared to the solids and liquids. The shape of a body around which a fluid (liquid or gas) can easily flow, offering minimum friction, is called streamlined shape. In nature, the body of fishes is streamlined such that they encounter least friction in water. Even a swimmer tries to streamline his body as far as possible so that he faces least friction due to water.

The body of boats and ship is also streamlined so that they encounter minimum friction while moving through water. The body of automobiles and aeroplanes is streamlined so that they encounter least resistance through air)



Fluid friction : The force of friction due to air and water (and other fluids) is called fluid friction. It also called 'Drag'

When cars and aeroplanes move at very high speeds, their motion is opposed by friction offered by the air molecules surrounding them. Drag, opposes the motion of the vehicle. The same applies to ships and boats.

2.6 ADVANTAGES OF FRICTION

There are numerous advantages of friction. Without friction, life would be impossible! You have learnt about the advantages of friction in earlier classes.

- (i) It is because of friction that we can walk, drive, open doors, turn taps, and write.
- (ii) We use screws and nails to keep pieces of furniture together. The screws and nails to do not slip off because of the friction between the wood and the metal surface of the screw.
- (iii) Bed sheets remain on the bed because of friction.
- (iv) You can sit on a chair without sliding off because of friction.

From what has been discussed above, it may appear that if there were no friction, our life would have been much easier and we would not have to spend energy in overcoming the frictional resistance.

This is not true. As a matter of fact, it is only because of friction that we are able to move around. Try to run on a very smooth surface and see what happens. As we step forward, friction opposes the forward force, so that the foot does not slip forward (Figure). When we raise our heel again to take another forward pace, the friction prevents the front part of the shoe from moving back.



Friction makes walking possible

On account of the friction between the ground and the rubber tyre of a bicycle, the latter can move forward. In the absence of friction between the wheels and ground, the wheel are unable to roll. That is why the wheels of a bicycle and other vehicles are treads to increase friction. To stop the bicycle, we use the opposing frictional force between the brake blocks and the wheel rim. So if an object started moving, it would never stop if there were no friction. It would be impossible to write with a pen or pencil without friction between pen and the writing pad. Friction holds a screw in wood. It also enables us to use nails to fix boards together. If friction were eliminated, dishes would slide off the table unless the table were perfectly in level. Thus with out friction, our life would have been in reality very inconvenient. Imagine, what would happen if there were no friction?

Looking at advantages and disadvantages of friction in our life, it can be rightly said that **friction is a necessary evil**.

Illustrations

Illustration 1

Give two examples to show that friction can also produce heat?

Solution

- (i) When we vigorously rub our palms together for a few minutes we feel warm.
- (ii) When we strike a matchstick against the rough surface, it catches fire due to friction.

2.7 DISADVANTAGES OF FRICTION

- (i) In machinery and automobiles, where there are moving parts, friction causes them to heat up. Heating up of the parts results in a waste of energy and fuel.
- (ii) Friction also causes wear and tear of the moving parts.
- (iii) Wear and tear due to friction depends on two factors. The roughness of the two surfaces in contact and the amount of time the two surfaces rub against each other. Wear and tear of an object is not desirable because it reduces its life.

Whenever there is a relative motion of two surfaces in contact, there is frictional resistance. When a body moves over another, it has to overcome friction. This needs energy. Hence, some energy is always wasted in overcoming friction. When two parts of a machine rub against each other, heat is produced, and the efficiency of the machine decreases. There will be greater wear and tear in different parts of a machine due to friction. Thus friction reduces the efficiency of machines.



FRICTION PLAYS AN IMPORTANT ROLE IN OUR DAILY LIFE

(i) Without friction we would slip and fall every time we attempt to walk or run. There is very little friction on a wet polished floor. That is why it is easy to slip on such a floor.



- (ii) Friction causes nails and screws to hold on to walls.
- (iii) It would not be possible to light a matchstick without friction between its head and the side of the match box.
- (iv) Cars and buses are able to run on roads because of friction between the tyres and the road.
- (v) Without friction writing on paper would be impossible as the tip of the pen will slip on paper.
- (vi) It is because of friction between the brake 'shoes' and wheels that bicycles and auto mobiles stop when brakes are applied.

FRICTION IS A DEMERIT TOO IN SOME CIRCUMSTANCES:

- (i) The heat produce in the moving parts of machinery due to friction results in wear and tear of the parts.
- (ii) Forest fires are caused due to friction between branches of trees rubbing against each other.
- (iii) Tyres of vehicles and soles of footwear wear out because of friction (figure).



Worn out sole of a shoe

(iv) Energy is wasted in overcoming the force of friction.

2.8 METHODS TO REDUCE FRICTION

- (i) Friction between moving parts is usually reduced by introducing a substance between the moving surfaces. This process is called lubrication. The substance introduced is called a lubricant. Common lubricants are oil and grease.
- (ii) Ball bearings are also used to reduce friction.
- (iii) By Polishing.
- (iv) By Streamlining.
- (v) By Powdering.

2.8.1 Ways to Reduce Friction

(i) Streamlined Bodies : Air and water offer the maximum friction. Objects moving in air or water have streamlined bodies to reduce friction. Birds, cars, aeroplanes and rockets have special streamlined bodies to reduce air resistance. Ship, fishes, boats and submarines are broad in the middle and narrow in front and at the back. So they faces least friction produced due to water current.



Streamlined shapes help to reduce friction

- (ii) Polishing : Polishing of rough surfaces also reduce friction If the surfaces that are in contact are rough, there is more friction. Hence to reduce friction, the surfaces in contact are kept smooth and polished. It is worth noting that if the two surfaces in contact are of the same metal, the friction increases on polishing the two surfaces. This is why the bearings and the axle are made of different metals.
- (iii) Wheels : If a suitcase is fitted with wheels, it is easier to move it because the friction between the wheels and the ground is less. Thus, wheels reduce friction.



Wheels reduce friction

- (iv) Lubricants : Use of lubricants make the surface smooth. In machines, friction is reduced by using lubricants such as oil, grease or graphite powder. The lubricant fills the minute unevenness of the two surfaces and separates them by forming a very thin layer in-between. This layer offers very little resistance and as a result, the friction gets reduced.
- (v) **Ball Bearings or Roller Bearings :** They are made in various designs to reduce friction. They reduce friction because rolling friction is smaller than sliding friction. These bearings are also lubricated to further improve their function.



Ball bearing and rolling friction

Ball bearings change sliding friction to rolling friction.

Ball bearings are used in most mechanical structures which have moving parts.

Small metal balls made of stainless steel, brass, ceramic, etc. are placed between moving surfaces (the surfaces can be flat or cylindrical) to reduce friction shown in figure.

- (vi) Anti-friction Metals : When steel slides over an alloy of lead, the friction is less than when steel slides on steel. Bearing are sometimes packed with such an alloy.
- (vii) Air Cushion : By separating the surfaces by an air cushion, a hovercraft can travel over rough land, swamp or sea. Here, as the moving object does not come in contact with the other solid surface, the frictional forces are reduced to a very great extent.





Illustration 2

Can we reduce friction to zero by polishing surfaces or using large amount of lubricants?

Solution

Friction can never be entirely eliminated. No surface is perfectly smooth. Some irregularities are always there.

2.8.2 Methods to increase friction

- (i) Making the surfaces rough. For example, the tyres of vehicles have treads (there are the designs that you can see on the tyre surface which increase the friction between the tyre and the road).
- (ii) Increasing the mass of the object that is moving.



Figure: Tyres have treads

2.9 FRICTION : A NECESSARY EVIL

It may appear that since the force of friction always opposes motion, it is always a curse. This is not so, because very often the force of friction is also a boon or, as we often say, a necessary evil. In fact, life would have been almost impossible if there were no friction. Friction helps us to walk and to drive our vehicles. It also helps us to produce heat.

In an effort to walk, we push the earth backward. In return, the earth pushes us forward and we are able to walk. On a highly polished floor, there is a very little grip between the floor and our shoes due to lack of friction. So, on a polished floor, the moment we try to push the earth backward, we slip and fall. So, it is friction that helps our feet to grip the road and enables us to walk. We even provide corrugations on the soles of our shoes to increase friction between our feet and the ground.



The corrugations on the soles of our shoes help us to have a better grip on the road

You must have seen that tyres of all new vehicles have many treads or corrugations on them. The treads on the tyres increases friction between tyre and the road. When the treads on a tyre get worn out, it loses its grip on the road and the vehicle tends to skid.



Treads on tyres help them to have a better grip on the road

Again, we make use of friction while applying brakes to our bicycle. When we apply brakes to our bicycle, we are really clamping rubber blocks against the revolving rim of the wheel. The resulting friction stops the movement of the wheels.



Friction stops the movement

Sometimes, we also use different materials to increase friction. For example, trolley Wheels have rubber washers. The use of wet surfaces generally reduces friction. Therefore, friction can be increased by making the surfaces dry. A wet glass tends to slip more easily from our hands than a dry one. We can increase the grip by increasing the pressure on surfaces in contact. Thus, when any object starts slipping from our hand, we hold it more firmly. This results in an increase of friction between that object and our hand.



Illustration 3

Aeroplanes are given special shapes why?

Solution

All vehicles are designed to have shapes which reduce fluid friction. Aeroplanes have special shapes to reduce air friction.

Illustration 4

Give an example that friction depends upon type of contact.

Solution

Throw a coin on a rough surface it stops after some time. Now throw it in the same way on smooth surface it stops after a longer time as there is less friction in later case.

Illustration 5

Can friction act on a body which is at rest? Which friction is it ?

Solution

Yes, Static friction

Illustration 6

Which friction acts when surfaces in contact are in motion.

Solution

Kinetic friction

Illustration 7 Write some methods to reduce friction?

Solution

(a) Polishing (b) Lubricating (c) Streamlining (d) Use of ball bearings

Illustration 8

Write methods to increase friction.

Solution

- (a) Making the surfaces rough or treading.
- (b) Increasing normal contact force between the surfaces.

Illustration 9

Heating effect due to friction is undersirable why?

Solution

Because

- (a) there is wastage of mechanical energy.
- (b) Efficiency is reduced.
- (c) Due to heating parts of machines may damage.

Illustration 10

Why we use 'ball bearing'?

Solution

This is due to the fact that rolling friction is smaller than the sliding friction and ball bearing changes sliding friction to rolling friction.

LET US RECAPITULATE

Friction: The force which opposes the relative motion between two surfaces in contact is called friction.
 The force of friction always opposes the applied force that may be a push or pull.

Friction is caused by the irregularities on the two surfaces in contact. Irregularities on the two surfaces lock into one another (interlocking) causing friction.

- Spring Balance: It is a device used for measuring the force acting on an object. It consists of a coiled spring, a pointer moving on a graduated scale. When a force is applied, stretching of spring takes place. The reading on the scale indicated by the pointer gives the magnitude of the force.
- Static Friction: The force required to overcome friction at the instant an object just starts moving from rest is a measure of static friction.
- Rolling Friction: When a body rolls over the surface of another body, the resistance to its movement is called rolling friction. Rolling reduces friction.
- Sliding Friction: When one body slides over the surface of another body, the resistance to its motion is called sliding friction. It is easier to roll than to slide a body over another. Common example is use of ball bearing between hubs and the axles of various machines.

Factors Affecting Friction:

- Friction depends on the nature of surfaces in contact.
- Friction is more between rough surfaces and less in smooth surfaces.
- Friction depends on how hard the two surfaces are press together.
- Friction is independent of the area of contact.

Friction: A necessary Evil

- Friction is essential for doing various activities of our daily life.
 - We could not hold articles such as glass tumbler and other things without friction. It becomes very difficult to hold a greasy glass.
 - We could not write with a pen or pencil if there is no friction.
 When we write with chalk on the blackboard, its rough surface rubs off some chalk particles which stick to the blackboard. It helps us to read what is written on the blackboard with a chalk
 - Friction helps objects to move, stop or to change the direction of motion. We cannot walk without friction.
 - Without friction no building could be constructed.

• Friction is an evil:

- It wears out materials. For example, soles of shoes, ball bearings, steps of a stair, parts of machines etc.
- Friction produces heat. When a machine is operated, heat generated causes much wastage of energy.

- We deliberately increase friction in some cases to get the desired results. For example:
 - Soles of shoes are grooved. It is done to provide the shoes better grip on the floor, so that we can safely walk.
 - The treated tyres of cars, trucks, buses, bull-dozers provide better grip with the ground.
 - Bicycles, scooters and other automobiles are provided with the brake system. When we press the brake lever, brake pads arrest the motion of the rim due to friction. The wheel stops moving.
- Sometimes we want to minimise the friction. Friction can be reduced by applying fine powder as in case of carrom. Oil, grease or graphite is applied between the moving parts of a machine to reduce friction. These things avoid interlocking of irregularities that lead to reduction of friction to a great extent. Sometimes an air cushion between the moving parts is used to reduce friction.
- Lubricants : The substances which reduce friction are called lubricants. Lubricants form a thin layer on the moving surfaces. So, they do not directly rub against each other.



- The wheel is said to be one of the greatest inventions of mankind.
- Fluids: In Science, the common name of gases and liquids is fluid.
- Fluid Friction: The force exerted by fluids on objects in motion through them is called fluid friction. The frictional force exerted by fluids is also called drag.
- The frictional force on an object in a fluid depends on
 - its speed with respect to the fluid,
 - the shape of the object, and
 - the nature of the fluid.
- To overcome drag objects are provided with special shape called streamlined. For example, shape of an aeroplane, a bird and a fish.







Fish

Streamlined shapes help to reduce friction.

Aeroplane

CC	NCEPT APPLICATION LEVEL - I [NCERT Questions]
	SECTION-A
Q.1	Fill in the blanks :
	(a) Friction opposes the between the surfaces in contact with each other.
	(b) Friction depends on the of surfaces.
	(c) Friction produces (d) Sprinkling of powdor on the carrom board friction
	(e) Sliding friction is than the static friction.
Ans.	(a) relative motion (b) nature (c) heat (d) reduces (e) less
Q.2	Four children were asked to arrange forces due to rolling, static and sliding friction in a
	decreasing order. Their arrangements are given below. Choose the correct arrangement :
	(A) rolling, static, sliding (B) rolling, sliding, static
A	(C) static, sliding, rolling (D) sliding, static, rolling
Ans.	(C) static, sliding, rolling
Q.3	Alida runs her toy car on a dry marble floor, wet marble floor, newspaper and towel spread on the floor. The force of friction acting on the car on different surfaces in increasing order will be (A) wet marble floor, dry marble floor, newspaper, towel (B) newspaper, towel, dry marble floor, wet marble floor (C) towel, newspaper, dry marble floor, wet marble floor
Ans	(A) wet marble floor, dry marble floor, newspaper
AII5 .	(<i>T</i>) wet marble nool, ary marble nool, newspaper, tower
Q.4	Suppose your writing desk is tilted a little, a book kept on it starts sliding down. Show the
	direction of frictional force acting on it.
Ans.	The book moves downwards. The frictional force is acting opposite to the movement of book. So it acts upwards.
Q.5	You spill a bucket of soapy water on a marble floor accidently. Would it make it easier or more
	difficult for you to walk on the floor ? Why ?
Ans.	The layer of soap makes floor smooth due to which the friction is reduced and the foot cannot make a proper grip on the floor. Therefore it is difficult to walk on a soapy floor and we start to slip.
Q.6	Explain why sportsmen use shoes with spikes.
Ans.	Sportsment use shoes with spikes to increase the friction between shoes and the surface. The shoes with spikes do not slip while they run or play.
Q.7	Iqbal has to push a lighter box and Seema has to push a similar heavier box on the same floor. Who will have to apply a larger force and why?
Ans.	The heavy object will be pressed hard against the opposite surface and produces more friction. So Seema a will have to apply a larger force due to more friction.
Q.8	Explain why sliding friction is less than static friction.
Ans.	The two sliding objects find less time to get interlocked against each other (objects and irregularities of surface). So they get less friction. Therefore sliding friction is always less than the static friction.
	PAGE#53

Q.9 Give examples to show that friction is both a friend and a foe.

Ans. Examples to show that friction is a friend and a foe :

Friction is a friend

- (i) Friction allows us to grip and catch different objects.
- (ii) It helps us to walk comfortably on the surface.
- (iii) It helps to minimise the speed or to stop the moving objects.
- (iv) It helps to write on paper and blackboard.
- (v) The things do not move from their place due to the friction between the surfaces.

Friction is a foe :

- (i) Friction causes wear and tear in objects.
- (ii) It causes damage to the parts of machines.
- (iii) The machines or tools require regular maintenance due to which a lot of money is wasted.
- (iv) It reduces the speed of moving objects, so more force is required.
- (v) It does not allows the free movement of objects.

Q.10 Explain why objects moving in fluids must have special shapes.

Ans. The object moving in fluids must have a special shape. This type of shape is called streamlined shape. The streamlined shape helps to overcome the friction between objects and fluids. The objects have pointed fronts with little broader middle portion which gets tapered at the back.

SECTION-B

• FILL IN THE BLANKS

- Q.1 The friction always ______ the direction of motion .
- Q.2 Friction also produces
- Q.3 All objects moving in fluids have ______ shape to reduce friction.
- Q.4 Smooth surfaces produce ______ friction than rough surfaces.
- Q.5 The substances used in machines to protect their surfaces from wear and tear caused by friction are called .
- Q.6 An air cushion between the moving parts is used to ______ friction.
- Q.7 Friction can never be entirely_____
- Q.8 Birds and fishes have ______ shaped body.
- Q.9 We pour a drop of oil on the hinges of door to ______ friction.

• TRUE/FALSE (Write True / False against each statement)

- Q.1 Friction always works in opposite direction of motion of the surface.
- Q.2 Irregularities between two surfaces interlock to produce friction.
- Q.3 Friction increases with increase in the smoothness of the surface
- Q.4 Soapy floor is slippery due to increased friction.
- Q.5 Friction is a necessary evil.
- Q.6 Spring balance is a device used for measuring the force:.
- Q.7 Sportsmen use shoes with spikes to increase the friction.
- Q.8 Smooth surface has less frictional force.

r

- Q.9 Fluids are only liquids.
- Q.10 Friction is always harmful for us.

		SECT	ION-C	
•	MULTIPLE CHOIC	CE QUESTION WITH	I ONE CORRECTAN	SWERS
Q.1	(A) lubrication	(B) ball bearing	(C) friction	(D) polishing
Q.2	Ball bearings are used (A) decrease friction (C) increase friction	to	(B) decrease surface a (D) increase surface an	irea rea
Q.3	Lubricants are used to (A) reduce friction	(B) increases friction	(C) make a surface oil	y (D) make a surface shiny
Q.4	Friction can be increas (A) making the surface (C) both (A) and (B)	sed by e rough	(B) increasing the mas(D) None of these	s of object
Q.5	When a bicycle travels	s on a rough surface, its	speed	
0.6	(A) increases	(B) decreases	(C) remains the same	(D) None of these
Q.0	(A) smooth	(B) rough	(C) very rough	(D) hard
Q.7	The frictional force (A) increases, decreases (C) increases, increases	with the	in roughness of (B) decreases, decreases, decreases (D) Both (B) and (C)	f the surfaces. se
Q.8	The maximum force o (A) limiting friction	f friction, when the body (B) rolling friction	just begins to move is k (C) static fiction	nown as the (D) dynamic friction
Q.9	The friction that exists (A) dynamic friction	between a surface slidin (B) rolling friction	ng on another surface is c (C) static friction	alled the (D) limiting friction
Q.10	The special shape of the (A) streamlining	ne body due to which it ex (B) friction	xperiences least fluid frie (C) buoyancy	ction is called (D) upthrust
Q.11	Suppose you writing d correct direction of frid	esk is tilted a little. A boc ctional force acting on it,	ok kept on it, starts sliding is	g down. The figure, showing the
	ion	Friction	ation	Friction
	(A) Frichte	(B)	(C) Frict	(D)
Q.12	Friction, that exists bet called	tween two surfaces in co	ntact, when there is no re	elative motion between them, is
	(A) sliding friction	(B) static friction	(C) viscous drag	(D) rolling friction
Q.13	The energy required to (A) sound energy	overcome friction is ma (B) heat energy	inly converted into (C) light energy	(D) chemical energy

,

Q.14	Out of the following, (A) water	the better lubricant to be	e used in the moving part (C) shalls never der	s of machine, is
	(A) water	(B) alf	(C) chaik powder	(D) turpentine on
Q.15	Force of friction is mo	ore in		
	(A) marble tiles	(B) wooden floor	(C) playground	(D) glass table
Q.16	Once a body starts mo	oving on table, the friction	on which comes into pla	y is
	(A) static friction		(B) sliding friction	
	(C) limiting friction		(D) None of these	
Q.17	The force of friction t	hat comes into play whe	en one body rolls over an	nother surface, is
	(A) sliding friction		(B) limiting friction	
	(C) rolling friction		(D) static friction	
Q.18	These days we use su	itcases with wheels bec	ause	
	(A) they look smart		(B) they are easy to c	carry
	(C) they make less no	ise	(D) none of these	
Q.19	Tyres have cut groove	es in them		
	(A) to increase friction	1	(B) to decreases frict	ion
	(C) to make them loo	k attractive	(D) to save rubber	
Q.20	Why we use circular t	yres		
	(A) They require less	material	(B) Rolling friction is	smaller than sliding friction
	(C) It is easy to inflate	the circular tyres	(D) Due to some seas	son other than these listed above
Q.21	1 m^2 area is equal to:			
	(A) 100cm^2	(B) 1000cm^3	(C) 10000 cm^2	(D) $10^{-4} \mathrm{cm}^2$
Q.22	Type of contact force	s can be		
	(A) Tension force	(B) Normal force	(C) Muscular force	(D) All of these
Q.23	When we apply a sma	all force on an object pl	aced on a rough table su	ch that object does not moves at
	all than the kind of fri	ction force between obj	ect and table is	5
	(A) kinetic friction			
	(B) rolling friction			
	(C) both rolling and ki	netic friction		
	(D) neither rolling nor	kinetic friction		
Q.24	A friction cannot act th	rrough		
	(A) empty space		(B) touching	
	(C) touching with met	al rod	(D) touching with a w	vooden rod
Q.25	A force that opposes t	he motion of one surfac	ce sliding over another is	called
	(A) friction	(B) newton	(C) Lubrication	(D) fall bearing

~

Q.26 What can be inferred regarding the frictional force in the following figures.



CONCEPT APPLICATION LEVEL - II

.

VERY SHORT ANSWER TYPE QUESTIONS

Q.1 Ans.	What is force of friction? The force acting on a moving body which is equal and opposite to the direction of motion is called force of friction.							
Q.2	What is the direction of frictional force?							
Ans.	The direction of frictional force is opposite to the relative motion between the surfaces.							
Q.3 Ans.	How many types of friction are there? There are four types of friction: (i) Static friction (ii) Sliding friction. (iii) Rolling friction (iv) Limiting friction							
Q.4	Which is less sliding friction or static friction?							
Ans.	Sliding friction is smaller than the static friction.							
Q.5	Why is it difficult to move on a wet marble floor?							
Ans.	Wet marble floor has less friction, so it is difficult to move on it.							
Q.6	Why does a matchstick catch fire when it is rubbed on a rough surface?							
Ans.	Matchstick catches fire due to heat developed by friction.							
Q.7	Write one harm of friction.							
Ans.	Friction wears out the materials like machine parts.							
Q.8	Why do the tyres of cars and trucks are treaded?							
Ans.	The treaded tyres of cars and trucks provide better grip with the ground.							
Q.9	What do you mean by lubricants?							
Ans.	The substances which are used to reduce friction are called lubricants.							
Q.10	Can we eliminate friction completely?							
Ans.	No, we cannot eliminate friction completely.							
Q.11	What is used to reduce friction in machines where lubrication are not advisable?							
Ans.	Air cushion.							
Q.12	Name two methods of reducing friction.							
Ans.	(i) By rolling (ii) Lubricating.							
Q.13	What is drag?							
Ans.	The frictional force exerted by fluids is called drag.							
Q.14	What are fluids?							
Ans.	Commonly gases and liquids are called fluids.							

CH-2: FRICTION

- Q.15 What does frictional force exerted on an object in a fluid depend on?
- Ans. Friction depends on the speed with respect to the fluid, the nature of fluid and the shape of the object.
- Q.16 Name the special shape given to objects moving in fluid.
- Ans. Streamlined shape.
- Q.17 Name some examples which have streamlined body.
- Ans. Boats, aeroplanes and ships.
- Q.18 When does rolling friction come into play?
- Ans. When a body rolls on other body then rolling friction come into play.
- Q.19 What a spring balance measures?
- Ans The magnitude of the force.
- Q.20 Why we fall down when we step on a banana peel?
- Ans. The banana peel reduces the friction between the feet and the road.

SHORT ANSWER TYPE QUESTIONS

- Q.21 What is the cause of friction?
- Ans. Friction is caused by the irregularities on the two surfaces in contact. The irregularities on the two surfaces lock into one another. Due to the interlocking of two surfaces friction arises.
- Q.22 What is a spring balance?
- Ans. Spring balance is a device used for measuring the force acting on an object. It contains a coiled spring. The spring gets stretched when a force is applied on it. Stretching of the spring is measured by a pointer moving on a graduated scale. The reading on the scale gives the magnitude of force.



Spring balance.

- Q.23 How does the friction get affected by the nature of surface?
- Ans. Nature of surface is the major factor which affects the friction. When we attempt to move on any surface, we have to apply a force to overcome the interlocking of the surfaces. On rough surfaces, there are a larger number of irregularities. So the force of friction is greater if a rough surface is involved.

CH-2: FRICTION

Q.24 What are static and sliding frictions?

- Ans. The force required to overcome friction at the instant an object starts moving from rest is a measure of static friction. On the other hand, the force required to keep the object moving with the same speed is a measure of sliding friction.
- Q.25 Which is smaller static friction or the sliding friction and why?
- Ans. When the object starts sliding: the contact points on its surface, do not get enough time to lock into the contact points on the floor. So the sliding friction is slightly smaller than the static friction.
- Q.26 The soles of our shoes get worn out after a period of time. Explain why?
- Ans. The soles of our shoes get worn out after a period of time due to friction. When we walk on the road, then the friction arises. Our shoes have to overcome friction to walk due to which our shoes get worn out slowly.
- Q.27 Our hands become warm when we rub them. Why?
- Ans. When we rub our hands with each other the friction arises between two hands. The friction produces heat, this heat makes our hands warm. That is, why our hands become warm when we rub them. We can feel this warmth by touching our hands on our face.
- Q.28 Mention three examples which shows that friction produces heat.
- Ans. Some examples are following which show that friction produces heat:
 - (i) Warming of our palms when we rub them.
 - (ii) Jar of a mixer becomes hot when it is run.
 - (iii) Warming of the parts of a machine when it is operated.
- Q.29 We observe that in some cases we want to increase friction. Explain why.
- Ans. If we do not increase friction, vehicles will slip on the roads and they will never stop. We need to increase friction for better grip and to control the speed of the moving objects. It is not easy to walk and write without friction. We increase friction by making roads with concrete and by applying brakes in vehicles to stop them.
- Q.30 Why do we need to decrease friction and how it can be decreased?
- Ans. Friction is harmful in some of the cases. It causes a lot of wear and tear in objects. It also causes damage to the machine parts. So we need to decrease the friction. It can be decreased by rolling, sliding and lubricating the surface in contact. We use ball bearings, wheels and lubricants like grease, oils and creams to decrease the friction.
- Q.31 Friction is called a necessary evil. Why?
- Ans. Friction is called a necessary evil because we cannot do anything without friction while it also shows ill effects. No movement would come to an end without friction. Nobody would be at rest without friction. Friction is necessary for making grip and bringing movements at rest.

LONGANSWER TYPE QUESTIONS

Q.32 Explain the advantages and the disadvantages of friction.

Or

Explain in detail that friction is called a necessary evil.

Ans. Advantages of friction :

- (i) We can not write with a pen or pencil, if there were no friction.
- (ii) We can not write on the blackboard with a chalk, if there were no friction.
- (iii) If an object started moving, it would never stop, if there were no friction.
- (iv) The vehicles cannot be started or stopped, *if* there were no friction.
- (v) We can not fix a nail on the wall or tie a knot without friction.

Disadvantages:

- (i) It wears out the materials whether they are screws, ball bearings or soles of shoes.
- (ii) The shoes worn out due to friction.
- (iii) Friction also produces heat. When a machine is operated, heat is generated that causes ,wastage of energy.
- (iv) The tyres of cars, buses and trucks, etc., also worn out due to friction.
- (v) Friction reduces the speed due to which more force is required.

In this way, we see that friction is harmful as well as useful so it is called a necessary evil.

- Q.33 Write some methods used to reduce friction.
- Ans. Methods to reduce friction:
 - (i) By using fine powder on the surfaces like on carrom board.
 - (ii) By using oils in the tools or in machine parts.
 - (iii) By using grease between the moving parts of the machines.
 - (iv) By using graphite powder between moving parts of a machine.;
 - (v) By using air cushion between the moving parts in some machines where oils or lubricants may not be advisable.
- Q.34 Explain various types of frictions.
- Ans. There are following types of frictions:
 - (i) Static friction (ii) Sliding friction (iii) Rolling friction (iv) Limiting friction
 - (i) **Static friction:** The friction which is produced between two surfaces in contact with each other at the position of rest is called static friction. This type of friction is more powerful than others. It is' not easy to overcome the static friction. This type of friction needs a lot of energy to overcome.
 - (ii) **Sliding friction:** The friction which arises when two objects in contact are in relative motion is called sliding friction. It is lesser than static friction but more than rolling friction. In this type of friction irregularities of surfaces do not get enough time and get locked with each other as objects are already in motion.
 - (iii) **Rolling friction:** The friction arises when two bodies are rolling on each other is called rolling friction. Rolling movement of both objects do not allow the locking of irregularities, so it is the smallest friction of three types of frictions.
- Q.35 What is fluid friction? Write the factors on which fluid friction depends.
- Ans. The gases and liquids are called fluids. The friction exerted by fluids on the object moving through them is called fluid friction. The fluid friction is also called drag. The factors on which fluid friction depends are as following:
 - (i) The fluid friction of an object depends on its speed with respect to fluid.
 - (ii) The fluid friction of an object also depends on the shape of the object.
 - (iii) The frictional force due to fluids also depends on the nature of the fluid.

CH-2: FRICTION

Q.36 What would happen if there were no force of friction? Imagine and describe in your own words.

Ans. If there were no friction many problems could have been arise, as one cannot be able to walk if there were no friction at all. One could not write with pen or pencil, if there were no friction. When one is writing with chalk on the blackboard, its rough surface rubs off some chalk particles. So, we can see the writing on the blackboard. If any object just started moving, it would never stop. Had there been no friction between the tyres of the automobiles and the road, they could not be started or stopped or turned to change the direction of motion. One could not fix a nail in the wall or tie a knot. Without friction no building could be constructed.

Q.37 Describe some events when we have to reduce the friction.

Ans. We sprinkled fine powder on the carrom board. When a few drops of oil are poured on the hinges of a door, the door moves smoothly. A cycle or a motor mechanic uses grease between the moving parts of the cycle. In all the above cases, we tried to reduce friction in order to increase efficiency. When oil, grease or graphite is applied between the moving part of a machine, its thin layer is formed there and moving surfaces do not directly rub against each other. Interlocking of irregularities is avoided to a great extent. Movement becomes smooth. The substances which reduce friction are called lubricants. In some machines it may not be advisable to use oil as lubricant. There is an air cushion between the moving part that is used to reduce friction.



Powder is sprinkled on the carrom board to reduce friction

Q.38 How the fluid friction can be minimized?

Ans. It is obvious that when objects move through fluids, they have to overcome the friction acting on them. In this process they lose energy. Efforts are, therefore, made to minimize the friction. So objects are given special shapes. The idea of special shapes comes from nature. Birds and fishes have to move about in fluids all the time. Their bodies must have evolved to shapes which would make them not to lose extra energy in overcoming friction. Such shapes are called streamlined. This is the reason ships, aeroplanes and cases are given a shape which resembles the streamlined shapes of birds and fishes.

CONCEPT APPLICATION LEVEL - III [Previous Years]

Q.1 A toy car is released from point X of the ramp and travels towards point Y. What is/are the forces responsible for pulling the car towards point Y?



- (i) Weight of the car
 (ii) Earth's magnetic field
 (iii) Frictional force between the wheels and the ramp
 (1) (i) only
 (2) (i) and (ii) only
 (3) (ii) and (iii) only
 (4) All of these
- Q.2 A spring balance was used to measure the force needed to pull a wooden block across different surfaces. The table shows the results. The force is expressed in newton. In which of the following surfaces is the friction greatest ?

Floor surface	Force needed to just start moving
Carpet	8N
Glazed tiles	5 N
Polished wood	4 N
Door mat	10 N

(1) Carpet (2) Glazed tiles (3) Wood (4) Door mat

- Q.3 Which of the following doesn't reduce friction ?
 (1) Ball bearing
 (2) Lubricant
 (3) Rolling
 (4) Grooving and treading
- Q.4 The diagram given below shows a ball rolling down a slope. The ball finally comes to a stop by itself. Which of the following statements describes what most likely caused the ball to stop ?



- (1) The heat produced as a result of its motion
- (2) The speed produced as a result of its motion
- (3) The friction between the ball and the surface
 - (4) The energy produced as a result of its motion

Q.5 Read the given statements and mark the correct option.

Statement 1 : When a bicycle is in motion, the force of friction exerted by the ground on the two wheels is always in forward direction

Statement 2: The frictional force acts only when the bodies are in contact.

(1) Both statements 1 and 2 are true and statement 2 is the correct explanation of statement 1.

- (2) Both statements 1 and 2 are true but statement 2 is not the correct explanation of statement 1
- (3) Statement 1 is true but statement 2 is false
- (4) Statement 1 is false and statement 2 is true
- Q.6 Consider a vehicle moving on a horizontal road towards east. Neglect any force by the air, the frictional forces on the vehicle by the road
 - (1) Is towards east if the vehicle is accelerating
 - (2) Must be towards east
 - (3) Must be towards west
 - (4) None of these

Q.7 Read the given statements and mark the correct option.

Statement 1: It is difficult to move by a cycle along the road with breaks on.

Statement 2: The sliding friction is greater than the rolling friction

- (1) Both statements 1 and 2 are true and statement 2 is the correct explanation of statement 1
- (2) Both statements 1 and 2 are true but statement 2 is not the correct explanation of statement 1
- (3) Statement 1 is true and statement 2 is false
- (4) Both statement 1 and 2 are false
- Q.8 An object of weight W is pulled along a rough, horizontal surface by a force X. The force of friction is Y. Which diagram correctly shows the direction of these forces on the object?



- Q.9 Two blocks A and B are released at the top of a rough inclined plane so that A slides along the plane and B falls down freely. Which will have higher velocity on reaching the ground ?
 - (1)A (2)B
 - (3) Both will reach the ground with same velocity
 - (4) It depends on the coefficient of friction
- Q.10 John carried out an experiment to find out how different surfaces (P, Q, R and S) effect the distance a car travelling at 50 km/h needed to stop once the brakes are applied. The results are shown below :

Type of road surfaces	Р	Q	R	S
Stopping distance(m)	18	15	19	27

Which type of road wi	ill provide t	he most friction for the car to stop?	
(1) P	(2) Q	(3) R	(4) S

Q.11 The displacement-time graph of a body in motion is shown here. The corresponding velocity-time graph will be :



Q.12 The speed-time graphs for three vehicles X, Y and Z are shown. if x, y and z are the distances travelled by X, Y and Z respectively in 8 s, then which of the following comparisons is correct?



Direction (Q.No. 13 and 14) Refer to the given passage and answer the following questions : Ram jogs from one end X to the other end Y of a straight 300 m road in 2 minutes 30 seconds, and then

turns around and jogs 100 m back to point Z in another 1 minute. $X \bullet$ Z Y 300 m 4 100

- $\begin{array}{cccc} Q.13 & \text{What is Ram's average speed and average velocity while jogging from X to Y respectively ?} \\ (1) 1.0 \text{ m s}^{-1}, 1.0 \text{ m s}^{-1} & (2) 3.0 \text{ m s}^{-1}, 2.0 \text{ m s}^{-1} \\ (3) 2.0 \text{ m s}^{-1}, 2.0 \text{ m s}^{-1} & (4) 4.0 \text{ m s}^{-1}, 1.0 \text{ m s}^{-1} \end{array}$
- $\begin{array}{ccc} \text{Q.14} & \text{What is Ram's average speed and average velocity while jogging from X to Z respectively ?} \\ (1) 2.0 \text{ m s}^{-1}, 1.9 \text{ m s}^{-1} \\ (3) 1.0 \text{ m s}^{-1}, 1.0 \text{ m s}^{-1} \\ \end{array} \begin{array}{c} \text{(2) 5.1 m s}^{-1}, 9.1 \text{ m s}^{-1} \\ \text{(4) 1.9 m s}^{-1}, 0.9 \text{ m s}^{-1} \\ \end{array}$

Direction (Q.15 & 16) Refer the given passage and answer the following questions.

The graph in the figure shows the position of a body at different times.



Q.15	What is the spee	d of the body as it move	s from A to B?	
	(1) 1 cm/s	(2) 2 cm/s	(3) 3 cm/s	(4) 4 cm/s
Q.16	What is the spee	d of the body as it move	es from C to D ?	
	(1) 1 cm/s	(2) 4 cm/s	(3) 8 cm/s	(4) 2 cm/s

.

ANSWER KEY

CONCEPT APPLICATION LEVEL - I [NCERT Questions]

SECTION-B

•	FILL IN TH	IE BLAN	NKS					
Q.1	Opposes		Q.2	Heat	Q.3	Stream lined	Q.4	Lesser
Q.5	Lubricants		Q.6	Reduce	Q.7	Eliminated	Q.8	Stream lined
Q.9	Reduce		-					
•	TRUE/FAL	SE (Wri	te True	e / False agains	t each s	tatement)		
Q.1	Т	Q.2	Т	Q.3	F	Q.4	F	Q.5 T
Q.6	Т	Q.7	Т	Q.8	Т	Q.9	F	Q.10 F
				SEC	Г ІОN-С	1		
•	MULTIPLE	CHOIC	CE QUI	ESTION WIT	H ONE	CORRECTAN	SWERS	
Q.1	С	Q.2	А	Q.3	А	Q.4	С	Q.5 B
Q.6	А	Q.7	D	Q.8	А	Q.9	А	Q.10 A
Q.11	D	Q.12	В	Q.13	В	Q.14	D	Q.15 C
Q.16	В	Q.17	С	Q.18	В	Q.19	А	Q.20 B
Q.21	С	Q.22	D	Q.23	D	Q.24	А	Q.25 A
Q.26	А	Q.27	А	Q.28	С	Q.29	В	Q.30 A

SECTION-D

• MATCHING SKILLS :

Q.1	(i) d	(ii) a	(iii)b	(iv) e	(v) c
Q.2	(i) d	(ii) c	(iii)b	(iv) e	(v) a

.

C()NC	EPT	A	PPLI	CA	ATION	V.	LEVE	[-	III []	Pre	vious Year	:s]
Q.1	1	Q.2	4	Q.3	4	Q.4	3	Q.5	4	Q.6	1	Q.7 1	
Q.8	3	Q.9	2	Q.10	2	Q.11	1	Q.12	1	Q.13	3	Q.14 4	
Q.15	1	Q.16	4										

Notes
· · · · · · · · · · · · · · · · · · ·

~